	1. PRODUCT IDENTIFICATION		
TRADE NAME (as labeled):	LATICRETE MultiMastic #15 Tile Adhesive		
USE:	Tile Adhesive		
MANUFACTURER'S NAME:	LATICRETE PTY LTD 29 Telford Street Virginia. QLD. 4014		
For additional information: Web address: Poisons Information Number: Date prepared or revised:	07 38651599, 1800 331 012 www.laticrete.com.au 131126 08/05/12		
	2. HAZARDS IDENTIFICATION		
	he criteria of the NOHSC. Not classified as a Dangerous Goods substance according to the ADG ccording to the SUSDP. Not classified as a flammable or combustible liquid according to the criteria		

Risk Phrases: R36/37/38 Irritating to eyes, respiratory system and skin. R66 Repeated exposure may cause skin dryness and cracking.

Safety Phrases: S24 Avoid contact with the skin. S25 Avoid contact with eyes. S25 In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. S28 After contact with skin was immediately with plenty of soap. S36/37/38 Wear suitable protective clothing, gloves and eye/face protection.

------ 3. COMPOSITION / INFORMATION ON INGREDIENTS------

CHEMICAL NAMES	CAS NUMBERS	PERCENT
Calcium Carbonate	1317-65-3	30-65
Other ingredients determined at level not to be hazardous		To 100%

#### SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhalation: Vapour may cause slight irritation to upper respiratory tract. No adverse effects are anticipated from inhalation incidental to normal exposure.

Contact with eyes: Eye contact may cause slight, temporary eye irritation. If symptoms persist seek medical attention.

Contact with Skin: Short exposure not likely to cause significant skin irritation. Skin absorption is unlikely due to physical properties.

Swallowed: No hazards anticipated from ingestion incidental to industrial exposure.

### FIRST AID or EMERGENCY PROCEDURES

Page 1 of 4

### Material Safety Data Sheet

**Eye Contact:** Wash the eyes with large amounts of water for 15 minutes, occasionally lifting the lower and upper lids. If symptoms persist get medical attention promptly.

Skin Contact: Remove contaminated clothing. Promptly wash contaminated skin with water for 3-5 minutes and then soap or mild detergent and water. If symptoms persist seek medical attention promptly.

**Inhaled:** Safely move the exposed person to fresh air at once and allow to rest. Provide artificial respiration if breathing stops. Seek medical attention unless recovery is immediate.

Swallowed: If the person is conscious, give large amounts of water. Do not induce vomiting. Get medical attention immediately.

#### First aid facilities

Provide normal industrial first aid facilities, eye wash station and safety showers as appropriate.

#### Notes to Physician

Possible aggravated pre-existing conditions – none reported.

Suggested treatment for acute symptoms, known antidotes – Provide care and treatment based on the patients reaction to the exposure. For further information contact the; Poisons Information Centre 131126 in all states (New Zealand Dial 0800764766)

Chronic Health Effects: Prolonged or repeated skin exposure may lead to drying and cracking skin.

		5. FIRE FIGHTING N	NEASURES
Flash Point, °C (give method): Auto ignition temperature, °C:	Not flan N/A	nmable or combustible	
Flammable limits in air, volume %:	N/A	Lower (LEL)	Upper (UEL)
Fire extinguishing materials: <u>x</u> water spray <u>x</u> foam		<u>x</u> carbon dioxide <u>x</u> dry chemical	other:
Hazchem Code: Not allocated			
Material is not combustible. Product Special fire fighting procedures: W containers cool. Unusual fire and explosion hazards	ear SCB		is boiled off. g. Avoid body contact with substance run off. Keep fire exposed
		6. ACCIDENTAL RE	ELEASE MEASURES
Emergency Procedures – Spills and place in container. Avoid unnecessary			ection measures: Use absorbent material or scrape up dried material and ety glasses and impervious gloves.
Prevent from entering drains and wate	rways.		

Preparing wastes for disposal (container types, neutralization etc): Soak up with absorbent materials. Store in pails or drums. Bury in approved landfill or burn solid wastes in an adequate incinerator. If enters sanitary sewers, flush with large amounts of water.

Notify relevant authorities if it enters drains and waterways.

## Material Safety Data Sheet

**Disposal:** Recycle wherever possible or consult manufacturer for recycling options. Dispose of in an authorized landfill according to federal, state and local regulations.

Handle with suitable protective clothing. Avoid skin or eye contact. Check all containers are clearly labeled and free from leaks. Storage Requirement Store in a cool, dry ventilated place between 1-35 °C. Protect containers against physical damage and check regularly for leaks. Observe manufacturers storing and handling recommendations. No exposure standards for this product have been set OR not found in our records. Ventilation and engineering controls: If used externally, natural ventilation is generally adequate. If used in enclosed spaced with poor ventilation provide mechanical ventilation to comfort levels. Respiratory protection (type): No respiratory protection is should be required if good ventilation is maintained. Use respirators fitted with organic vapour filters to AS1715 & AS1716 in areas with high vapour concentrations. Eye protection (type): Use a chemical goggle or safety glasses with side shields or safety glass to AS1337. Gloves (specify material): Use impervious gloves, vinyl or rubber to AS2161 Other clothing and equipment: Wear clean, long-sleeved, body covering clothing. Work practices, hygienic practices: Familiarize the employees with the handling procedures in this section; also encourage prompt removal of contaminated clothing and clearing of contaminated areas. Vapor density (air=1): N/A Melting point or range, °C: N/A Boiling point or range, °C: 100 Specific gravity: 1.6 Solubility in water: Miscible Evaporation rate (butyl acetate = 1): N/A Vapor pressure, mmHg at 20 ° C: 0mm **pH**: 10 Appearance and odour: White paste, slight acrylic odour Stability: X Stable Unstable Conditions to avoid: Excessive heat and freezing Incompatibility (materials to avoid): Strong oxidizers and caustics. Hazardous decomposition products (including combustion products): (from burning, heating or reaction with other material): None

Page 3 of 4

## Material Safety Data Sheet

Hazardous polymerization:	May occur	X	_ Will not occur			
	11 . TOXICOLOGICAL INF	ORMATION				
No relevant product data found	12. ECOLOGICAL CONSI	DERATIONS				
May have an adverse effect on aquatic organisms if large amounts are released to waterways.						
	13. DISPOSAL CONSIDEF	RATIONS				
Dispose of all wastes in accordance with federal,	state and local regulations for	non-hazardo	ous chemical wastes			
	14. TRANSPORT CONSI	DERATIONS				
Requirements under the ADG code, IMDG code, o	or the IATA DG code do not a	pply to this p	roduct			
	15. REGULATORY INFOR	RMATION				
Label in accordance with the National Code of Pra SUSDP or the ADG Code is not required.	actice for the Labeling of Worl	kplace Subst	ance (NOHSC: 2012 (1994)): Labeling under the			
	16. OTHER INFORMATIO	ON				

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate. Persons dealing with the products referred to in this MSDS do so at their own risk since their actions are beyond our control. Laticrete Pty Ltd accepts no liability whatsoever for damage or injury arising from the use of the information contained in this document. This document should be made available to all operators who may come into contact with this product.